

SCM19A : 2 - w a y a c t i v e



Features

- New ATC designed and built dual suspension 25mm soft dome HF unit with precision alloy wave guide.
- "SL" spec bass driver with 75mm integral Soft Dome.
- 9kg optimised short-coil/long gap motor assembly.
- On-board grounded source 182 watt Class A/B Bi-amplifier.
- Active filters and overload protection.
- 6 year warranty.

Specifications

- Drivers :** HF ATC 25mm dual suspension Tweeter, Mid/LF ATC 150mm SL
- Matched Response :** +/- 0.5dB **Frequency Response (-6dB) :** 54Hz-22kHz
- Dispersion :** ±80° Coherent Horizontal, ±10° Coherent Vertical
- Max SPL :** 108dB
- Crossover Frequency :** 2.5kHz
- Connectors :** Male XLR
- Input sensitivity :** 1V
- Filters :** 2nd Order critically damped with phase compensation
- Overload Protection :** Active FET momentary gain reduction
- Fault Protection :** DC fault protection and thermal trip.
Fault indication on rear panel mounted LED
- Amplifier Output :** 150W LF, 32W HF
- Cabinet Dimensions (HxWxD) :** 980x370x344mm
(spikes add 25mm to height, grill adds 34mm to depth)
- Weight :** 31kg



Loudspeaker Technology Ltd

Gypsy Lane, Aston Down, Stroud, Gloucestershire GL6 8HR United Kingdom

Telephone 01285 760561 Fax 01285 760683

Email info@atc.gb.net Website www.atcloudspeakers.co.uk

ATC reserves the right to vary products and specifications without prior notice.